

**FXD63B200 | US2:FXD63B200**



SIEMENS LOW VOLTAGE SENTRON MOLDED CASE CIRCUIT BREAKER WITH THERMAL - MAGNETIC TRIP UNIT. STANDARD 40 DEG C BREAKER FD FRAME WITH STANDARD BREAKING CAPACITY AND NON INTERCHANGEABLE TRIP. MEETS UL 489 / IEC 60947-2 STANDARDS. 200A 3-POLE BREAKER (22KAIC AT 600V) (35KAIC AT 480V). SPECIAL FEATURES: NO LUGS INSTALLED. DIMENSIONS (W x H x D) IN: 4.5 x 9.5 x 4.

**Product**

Article Number (Market Facing Number)	FXD63B200   US2:FXD63B200
Product Description	SIEMENS LOW VOLTAGE SENTRON MOLDED CASE CIRCUIT BREAKER WITH THERMAL - MAGNETIC TRIP UNIT. STANDARD 40 DEG C BREAKER FD FRAME WITH STANDARD BREAKING CAPACITY AND NON INTERCHANGEABLE TRIP. MEETS UL 489 / IEC 60947-2 STANDARDS. 200A 3-POLE BREAKER (22KAIC AT 600V) (35KAIC AT 480V). SPECIAL FEATURES: NO LUGS INSTALLED. DIMENSIONS (W x H x D) IN: 4.5 x 9.5 x 4.

**Delivery information**

Export Control Regulations	AL : N / ECCN : EAR99
Standard lead time ex-works	20 Day/Days
Net Weight (lb)	8.803 lb
Product Dimensions (W x L x H)	Not available
Packaging Dimension	5.354 x 6.89 x 11.024
Package size unit of measure	in
Quantity Unit	1 Piece
Packaging Quantity	1

**Additional Product Information**

EAN	Not available
UPC	783643211278
Commodity Code	8536200020
LKZ_FDB/ CatalogID	LV10.1
Product Group	3741
Country of origin	Mexico
Compliance with the substance restrictions according to RoHS directive	Since: 04/03/2009
Returnable	Yes
WEEE (2012/19/EU) Take-Back Obligation	Yes
REACH Art. 33 Duty to inform according to the current list of candidates	

**Classifications**

	Version	Classification
eClass	5.1	27-37-04-09
eClass	6	27-37-04-09
eClass	7.1	27-37-04-09
eClass	8	27-37-04-09
eClass	9	27-37-04-09
eClass	9.1	27-37-04-09
ETIM	5	EC000228
ETIM	6	EC000228
ETIM	7	EC000228
UNSPSC	15	39-12-16-01